



APE Model 375K Drill Top Drive Auger

THE WORLD'S LARGEST PILEDRIVERS



SPECIFICATION	STANDARD	METRIC
MINIMUM DISPLACEMENT	9.15 C.I.	150 CC
MAXIMUM DISPLACEMENT	21.7 C.I.	355 CC
MAXIMUM HIGH SPEED FLOW	130 GPM	490 LPM
MAXIMUM LOW SPEED FLOW	225 GPM	850 LPM
TYPE	TWO SPEED AXIAL PISTON MOTOR	
OUTPUT TORQUE	375,000 FT-LB	508,000 N-m
SHAFT PULL-OUT	275,000 LBF	1,223,000 N
PRESSURE LOAD	275,000 LBF	1,223,000 N
OIL TYPE	80W90 EP OR GL-5	
OIL CAPACITY	23 GAL	87 LIT
DRIVE PRESSURE	0 - 4,700 PSI	0 - 324 BAR

Specifications may vary due to site conditions, specific hammer conditions or product set up.
Specifications may change without notice.
Consult the factory for details on any specific product (800) 248-8498.



WWW.AMERICANPILEDIVING.COM

(800) 248-8498

Ape@americanpilediving.com

Copyright © 2022 American Pilediving Equipment Inc. All Rights Reserved