



MODEL 33EX VIBRO

Driver / Extractor



- *Patented one piece helical gear/eccentric eliminates gearbox failures*
- *caused by broken pins, keys, bolts or splines found in all other vibros.*
- *Giant double roller spherical bearings for super long life*
- *Special valves available for clamp circuit operation from just two hoses*

Model 33EX Vibratory Driver/Extractor



SPECIFICATIONS: VIBRATOR

Model 33EX

Eccentric moment	48 kg-m (400 in-lb)
Frequency (variable)	0-2100 vpm
Centrifugal force	34 tons
Amplitude	15 mm (0.60 in)
Suspended weight (w/ univ. sheet clamp)	910 kg (2000 lbs)
Length	112 cm (44 in)
Width	53 mm (22 in)
Height with suppressor and clamp	110 cm (43 in)
Motor Pressure Rating	344 bar (5000 psi)
Flow at rated vpm	142 lpm (38 gpm)

Advanced, profit generating features that are years ahead of the competition:

- **Mounts and operates off backhoe hydraulics.**
- **Patented one-piece helical gear/eccentric eliminates gearbox failures caused by broken pins, keys, bolts or splines found in all other vibros.**
- **Giant double roller spherical bearings for super long life.**
- **Special valves available for clamp circuit operation from just two hoses.**
- **Computer-designed gearbox is perfectly balanced with the lowest center of gravity on the market.**
- **Heavy duty clamp cylinder.**
- **Low headroom suppressor housing.**



Corporate Offices:
7032 South 196th
Kent, Washington 98032 USA
(800) 248-8498 & (253) 872-0141 Fax (253) 872-8710

Visit our WEB site:
www.apevibro.com
e-mail: ape@apevibro.com

Due to constant improvements we must advise you to call APE for the latest available literature and specifications.